

Oil-Only Poly Blend Socks #WSO430 - 3" x 4', 30 socks/package



Poly blend-filled Oil-Only Socks contain and soak up petroleum-based fluids fast while repelling water.

- **Absorb Oils, Repel Water** — By selectively absorbing petroleum-based liquids and not water, these Socks take in more oil and can be left on the job longer. They also float for cleanup of waterborne hydrocarbons.
- **Contain and Soak Up Leaks or Spills** — Ideal for surrounding spilled fluids or wrapping around leaky machines. Easy and convenient to put into place. Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards. Flexible to conform around machine bases and offer a snug fit with no seepage.
- **Color-Coded** — Color-coding helps you visually identify the right sorbent for your needs. White designates Oil-Only sorbency and makes it easy to identify when saturated.

WSO430 Specifications

Dimensions:	ext. dia. 3" x 4' L
Shipping Dimensions:	22" W x 24" L x 18.25" H
Sold as:	30 socks per package
Color:	White
Composition:	Poly Blend
Recycled Content:	100% Post-Industrial Recycled Poly Blend Filler
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 106.6 oz. per sock
Weight:	30 lbs.
# per Pallet:	16
Incinerable:	Yes
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 121.9cm L
Shipping Dimensions:	55.9cm W x 61cm L x 46.4cm H
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 3.2 L per sock
Weight:	13.6 kg

WSO430 Technical Information

Warnings & Restrictions:

Color Variance Notice
Color may vary.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com