

AMMONIA TRAFFIC LANE

Ammoniated Carpet Pre-conditioner



PRESPRAY

Ammonia Traffic Lane is a special blend of ammonia, surfactants, brightening agents, and softeners that deliver powerful, reliable cleaning performance.

- **Non-foaming**
- **Self-neutralizing**
- **Effective on organic soiling**
- **Contains grease and oil breakers**
- **Available in: 4 L (1.06 US gal.), 20 L (5.28 US gal.) or 205 L (54.1 US gal.)**

READY TO TAKE ON ANY TOUGH TRAFFIC LANE SITUATION

DIRECTIONS FOR USE:

Pretest in an inconspicuous location for color fastness and fibre stability.

Pump-up or Power Sprayer:

Light Soil Conditions: Mix 1/3 gallon (1.26 L) of Ammonia Traffic Lane with 2/3 gallon (2.52 L) of warm to hot water to make a 1 gallon (3.78 L) ready to use solution (1:2 Dilution).

Heavy Soiled Conditions: Mix 1/2 gallon (1.89 L) of Ammonia Traffic Lane with 1/2 gal (1.89 L) of warm to hot water (1:1 Dilution).

Keep this product out of reach of children. Read the Material Safety Data Sheet and Product Label before using. Take the necessary precautions dictated by the label to ensure that your health and that of your customers' is protected.



Diluted pH: 10.0
Dilution Ratio: 1:2

For best results: Pile lift or vacuum carpets prior to cleaning. Spray diluted Ammonia Traffic Lane solution onto carpet at a rate of 800 - 1,000 square feet per gallon (3.78 L). Agitate presprayed area using a mechanical brush or carpet groomer. Allow 10 minutes dwell time, then rinse with Esteam Fibre Rinse solution in conjunction with hot water extraction.

NOTE: Do not mix Esteam Ammonia Traffic Lane with any other chemical product.

www.esteem.com



1-800-653-8338

See Material Safety Data Sheet at www.esteem.com/msds.php