

Airmovers

Sahara Pro X3 TurboDryer

Versatile applications and legendary durability. All the features you need: three speed settings, low amp draw, built-in GFCI outlets for daisy-chaining, a rugged stackable rotomolded housing, and an integral carry grip/cord wrap.

Features

- Low amp draw—4 amps max!
- Daisy-chain capability with built-in power outlet and circuit breaker
- Excellent versatility with 3 speeds and 3 operating positions – 0°, 45° and 90°
- Underside drying vent for drying under the airmover
- Quick disassembly for cleaning
- Easy-grip handle
- Stackable for storage

Specifications

- **Rated airflow:** 2700 CFM | 4587 CMH
- **Airflow velocity:** 2071 ft./min. | 631 M/min. (tested)
- **CFM per amp:** 235
- **CFM per 15 amp circuit:** 2817 CFM (tested)
- **Static pressure:** 1.28 in. | 3.25 cm
- **Dimensions (W × H × D):** 17 × 18.8 × 18.3 in. | 43 × 47.8 × 47 cm
- **Weight:** 27 lbs. | 12 kg
- **Amps:** 3A, 3.5A, 4A
- **Volts:** 115V
- **Frequency:** 60Hz
- **Power:** 0.33HP (motor rating)
- **Switch:** Recessed rotary
- **Operating positions:** 3 (0°, 45° and 90°)
- **Cord length:** 25 ft. | 7.6 m
- **Carpet clamp:** Available as accessory
- **Circuit breaker/GFCI:** Yes
- **Housing:** Rotomolded polyethylene
- **Safety:** Listed to UL/cULc standards
- **Xactimate:** WTRDRY

Sizes ▪ Options

- 112421 (F351): One unit