

Airmovers

Velo Pro Low Profile Airmover

Unbeatable versatility and portability. Precisely control power draw from 1.2–1.9 amps and daisy-chain up to 10 units on a single 15-amp circuit. A built-in kickstand provides a total of five operating positions. Don't need variable speed control? Chose the standard [Velo airmover](#).

Features

- Adjust amp draw from 1.2-1.9 amps in 0.1-amp increments to balance draw in limited power settings
- Variable speed control from 500 (min.) to 885 (max.) CFM.
- Daisy-chain capable with convenient dual outlet.
- Hour meter to track usage and maintenance intervals
- Patented outlet design ensures even, broad-path airflow for fast, consistent drying across all surfaces.
- Five operating positions. Dry floors, ceilings, walls and stairways quickly and efficiently.
- Great portability. Easily carry two units at once—or stack up to six on a hand truck.
- Easiest to maintain. Simply remove fasteners and lift out impeller assembly for cleaning.

Specifications

- **Amps:** 1.2–1.9 amps
- **Air movement:**
500–885 CFM
850–1504 CMH
- **Power:** 185W
- **Controls:** Variable speed with on/off switch
- **Static pressure:** 1.65 in. / H2O
- **Weight:** 18.6 lbs. | 8.4 kg
- **Dimensions (D × W × H):** 24 × 18 × 9 in. | 61 × 45.7 × 22.9 cm
- **Watts:** 185W
- **Fan:** 6 blade impeller-type
- **Sound level (avg.):** 69 dB
- **Construction:** Injection-molded housing, steel wire inlet and outlet grills.
- **Safety:** ETL listed to UL/cUL and CSA standards
- **Xactimate:** WTRDRY

Sizes ▪ Options

- 114969 (F505): One unit