



Hardwood Preservation GLOSS Finish

- Hardwood Floors
- Cabinets
- Furniture

Contents: One U.S. Gallon (3.79 Litres)

- Designed to be used as a preservation finish over an existing urethane finish over a hardwood floor
- Low solid blend of urethane and acrylic
- Serves as the wear coat and protects the original finish of the floor



Extraction Cleaning

- Vacuum floor thoroughly.
- Mask off transitions from wood to other types of floors.
- Mix one part Heavy Duty Hardwood Cleaner with 4 parts warm water in the cleaning machine. Adding a defoamer like Foamies to the waste tank is recommended for some machines and situations.
- With the solution pumping, the brush rotating and the vacuum turned on, begin moving the machine forward at a moderate speed. Reverse on the same line at the same speed. Then continue into the next area with the same procedure. Remove any standing solution with an absorbent flat mop.
- Mix one part Wood Fresh™ Hardwood Cleaner with 4 parts warm water in the cleaning machine
- Proceed to clean and neutralize the complete floor in the same manner as explained above.
- The cleaning and preparation steps are important. The dual cleaners both clean and treat the floor to make it more receptive to the Preservation Finish. Apply finish immediately after cleaning

approximately 1,000 sq. ft.

Apply Preservation Finish

- Let the customer choose Gloss or Satin finish. Solids may settle to bottom of gallon over time. Shake or stir before and during use.
- The finish may be applied with a dampened flat mop using either a clean cotton terry cloth cover or a microfiber cover. 30 minutes prior to applying the finish the container should be gently rocked to mix the ingredients.
- Start in the furthest area from your exit. Apply a small amount of finish in a 4 or 5 foot area, spreading it uniformly as you work your way back toward the exit door.
- If a second coat is desired, allow one hour before applying.
- Use abrasive cleaning method when applying finish to cabinets and furniture.



Helpful Hints

- Traffic: Allow one hour dry time before allowing stocking feet onto the finish. Allow 24 hours before shoe traffic and replacing furniture. Allow 48 hours before replacing rugs.
- Prequalify: The system emphasizes the importance of preserving the original finish so hopefully the customer will never have to go through the messy process of sanding and recoating their hardwood. This system does not make damaged or heavily scratched floors look like new. We suggest you

- Coverage: Approximately 1,000 sq. feet per gallon

INGREDIENT DISCLOSURE:

Water, Urethane Polymer, Acrylic Polymer, Tributoxo-ethyl Phosphate, Polyethylene Emulsion, Polypropylene Emulsion, Ethoxydiglycol, Triethylamine, Benzothiazolone.

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to www.hydroforce.com/sds for additional safety, regulatory and liability information.

WARNING

Keep out of reach of children.

HAZARD STATEMENTS:
Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS:
Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

ATENCIÓN

Mantener fuera del alcance de los niños.

INDICACIONES DE PELIGRO:
Provoca irritación cutánea. Provoca irritación ocular grave.

DECLARACIONES DE PRECAUCIÓN:
Lávase las cara, las manos y la piel con abundancia tras la manipulación.

Utilizar guantes/lentes de protección/instrumento de protección para los ojos/la cara. EN CASO DE CONTACTO CON LOS OJOS: Aclarar cuidadosamente con agua durante varios minutos. Quitar las lentes de contacto, si lleva y resulta factible. Seguir aclarando. Si la irritación ocular persiste: consultar a un médico. EN CASO DE CONTACTO CON LA PIEL: Lavar con agua y jabón abundante. En caso de irritación cutánea: consultar a un médico. Quitar las prendas contaminadas y lavarlas antes de volver a usarlas.

AVERTISSEMENT

Tenir hors de portée des enfants.

MENTIONS DE DANGER:
Provoque une irritation cutanée. Provoque une sévère irritation des yeux.

CONSEILS DE PRUDENCE:
Se laver le visage, les mains et toute surface de peau exposée soigneusement après manipulation. Porter des gants de protection/lunettes de protection/un équipement de protection des yeux/la visage. EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. Si l'irritation oculaire persiste: Consulter un médecin. EN CAS DE CONTACT AVEC LA PEAU: laver abondamment à l'eau et au savon. En cas d'irritation cutanée: Consulter un médecin. Enlever les vêtements contaminés et les laver avant réutilisation.

Made in the USA with globally sourced materials.
Hecho en los USA con materiales de origen mundial.
Fabriqué aux USA avec des matériaux provenant du monde entier.

See Safety Data Sheet (SDS):
www.hydroforce.com/sds
for additional safety and regulatory information.

Another fine product from Hydro-Force Manufacturing
4282 South 590 Street, Salt Lake City, UT 84123
1-3680 Odyssey Drive, Mississauga, ON L5M 0Y9
www.hydroforce.com | 800-658-5314

