





oroughly. ons from wood to other types of

- Vacuum floor thoroughly.

- Mask of thrankinos from wood to other types of floors.

- Mask of thrankinos from wood to other types of floors.

- Mask of the service of the claiming name of the desired part of the section of the section of the section of the section of the desired part of the desired par

Designed to be used as a preservation finish over an existing unerhane finish over a hardwood floor exception of the property of the property of the customer choose Gloss or Staff finish. Solids may settle to bottom rigidance with resilvate or staff finish. Solids may settle to bottom rigidance with resilvate or staff finish. Solids may settle to bottom rigidance with a dampened fill finish finish from the finish may be applied with a dampened fill finish finish from the finish the container should be gently rocked to mix the impredients.

Start in the furthest area from your exit. Apply a small amount of finish in a 4 or 5 foot area, spreading it unforthering any our work your way back.

Extraction Cleaning

• Vacuum floor thoroughly.

• Use abrassive cleaning method when applying finish to cabinets and furniture.

MAXING STREAMINE.

MAZING STREAMINE.



Helpful Hints

• Traffic: Allow one hour dry time before allowing

• Traffic: Allow one hour dry time before allowing

• Traffic: Allow one hour dry time before shoe traffic and replacing furniture. Allow 48 hours before replacing rugs.

• Prequality: The system emphasizes the importance of preserving the original finite is hopefully the customer will never have to go through the messy process of sanding and recoasting then bendwood. The process of sanding and recoasting their herdwood. Some standard floors look like new. We suggest you under promise and then over perform.

• Coverage: Approximately 1,000 sq. feet per gallon.

INGREDIENT DISCLOSURE: Water, Urethane Polymer, Acrylic Polymer, Tribu-toxyethyl Phosphate, Polyethylene Emulsion, Poly-propylene Emulsion, Ethoxydiglycol, Triethylamine, Dodoxynor-13, Celeareth-20, Oleth-10, Ammonium Hydroxide, Benzisothiazolinone.



HAZARD STATEMENTS: Causes skin imitation. Causes serious eye imitation.

PRECAUTIONARY STATEMENTS:
What face, hands and any exposed skip principly after bracking Weat
face, hands and any exposed skip principle, and the principle.

"It is present to the principle of soap and weather it shall initiation occurs. Get medical advice/attention, Table of constrained coloring and was forther ones.



INDICACIONES DE PELIGRO: Provoca initación cutánea. Provoca inita

CONSLIOS DE PRUDENCIA:
Lavarso la cara, las manos y la piel concienzudamente tras la
manipulación. Usar guaritestripas de protección/equipo de protec
para los opisals cara. EN CASO DE CONTIACTO CON LOS QUOS.
Aclarar cuidadosamente con agua durante varios minutos. Quitar

CONSIGUE DE PRUDENCE.

So loso l'es visage, les mains et foute surface de passa exponde

So loso l'es visage, les mains et foute surface de passa exponde

son de l'estate de la protection des paucides

visage, LE CAG DE CONTACT PARC LES YELEX nonce avec précaution

à l'ano pendant plusioner manulas. Efferier les derits de cordat a la direct de l'estate de l'estate

AVERTISSEMENT! MENTIONS DE DANGER: Provoque une irritation cutanée. Provoque une sévère irritation

See Safety Data Sheet (SDS):
www.shydroforex.com/bds
for additional slades and regulatory information.
Another fine product from Pydor-Force Narndsturling
A225 South 590 West, Saft Lake (City, UT 84123
1-3680 Odyssey Drive, Mississauga, ON LSM 079
www.hydroforce.com | 800-658-5314

