

## Flood Extractors

### HVE 3000 Flood Pumper

High vacuum and powerful lift pulls maximum water from carpet and pad fast while a clog-resistant, high-volume industrial pump delivers up to 50 gpm. A narrow profile and large rear wheels make transport easy. The unit can also be used with a truckmount to boost vacuum or intercept extracted water to keep truckmount tank from filling up.

### Features

- Clear-view first-stage filter lifts out for easy rinsing.
- A high flow, high volume clog-resistant sump pump handles up to ½ in. solids.
- Rugged construction. Low center of gravity provides balanced transport; easy on stairs!
- Use the HVE 3000 to bypass the truckmount waste tank for black water flood extraction to keep the tank clean.
- Accessories included One 25 ft. section of 2 in. vacuum hose with cuffs
- Dual vacuum blowers with 2 in. inlet ensures maximum airflow.
- Easy maneuverability – just pull on the hose! Slim profile to fit through the narrowest doors – only 22.5 in. wide.
- Large capacity waste tank. 12 gallon tank means fewer trips to the drain when you're not using the auto-pumpout system.
- Two auto-pumpout options: barbed outlet for a 1½ in. drain hose and a ¾ in. converter outlet fitting for use with a standard garden hose.
- Use the large toilet-height gravity drain for small jobs and easy tank cleanout.
- Exhaust air passes through HEPA filter. Helps to prevent the spread of contaminants and odors and conforms to 2015 IICRC S500 (13.3.3) recommendations.

### Specifications

- **Static pressure (Blower 1):** 8 in. Hg | 108 in. H2O
- **Static pressure (Blower 2):** 10 in. Hg | 136 in. H2O
- **Static Pressure (Both blowers):** 12 in. Hg | 164 in. H2O
- **Pumpout discharge rates:** 50 gpm (1.5 in. outlet); 12 gpm (0.75 in. outlet)
- **Dimensions (W × H × D):** 22.5 × 40.2 × 23.6 in. | 57.2 × 102.1 × 59.9 cm
- **Weight:** 132 lbs. | 60 kg
- **Volts:** 115V
- **Amps:**  
12A (Blower 1 + Pumpout)  
13.5A (+Blower 2)
- **Frequency:** 60Hz
- **Tank capacity:** 12 gal. | 45L
- **Power:** 115V
- **Safety:** ETL listed to UL/cUL and CSA standards.
- **Xactimate:** WTR EXT (+ & W)

### Sizes ▪ Options

- 107977 (F479): One unit