



# The Omniguard 5

## Differential Pressure Monitor

### ORDERING INFO

Omniguard 5  
Autodialer  
Remote Auxiliary Alarm  
External Hose Replacement  
Thermal Paper (box of 5)

### PART NUMBER

IOG4  
IOGAUTODIALER  
IOGALARM  
IOGHOSE10FT  
IOGP5



touch screen

### THE WATCHMAN IS IDEAL FOR

Abatement/Remediation Jobs  
Restoration Projects  
Construction Sites  
First Response & Epidemic Control

The Omniguard 5 differential pressure recorder is built in a completely self-contained package. This pressure monitor uses real time monitoring of differential pressure and/or vacuum level, with dual inlet ports to allow monitoring between two areas. Multiple reports available at the touch of a key and the view log on screen makes it easy to scroll through the entire memory contents. The USB Type-A port lets you save logs directly to a flash drive as an additional logging option and a second USB port supports PC communication for transferring job logs, real time monitoring and configuration editing.

### The Watchman

<b>Differential Pressure Range</b>	+/- 0.250 inches Water Column ( +/- 6.35 mm WC, +/- 62.5 Pascals)
<b>Accuracy</b>	+/- 0.003 inches Water Column or +/- 1% of reading whichever is greater
<b>Power Requirements</b>	85-240 VAC 50-60Hz 10W Max (with 6 ft power cord), Internal rechargeable 3.7 Volt Li-ion type battery
<b>Controls &amp; Display</b>	4.3" Color Touchscreen LCD (480 x 272 pixels)
<b>Burst Pressure</b>	3 psi (20 kPa) on either inlet nozzle
<b>Alarm</b>	Two programmable alarm settings, 95db audible alarm and red bordered on-screen warning indicate alarm condition
<b>Housing</b>	copolymer polypropylene with polycarbonate window in the lid, stainless steel hanging hook
<b>Pressure Inlets</b>	(2) 3/16" OD barbed hose connectors, 10 ft of pressure hose provided
<b>Size/Weight</b>	9.25" x 7.5" x 4.5"; 6 lbs.