



426

VIBAC® BOPP BOX SEALING TAPE 426

This Utility Grade packaging tape used for carton sealing, splicing, bundling, and other lightweight packaging applications. This product has a conformable film backing with a consistent pressure sensitive hot melt adhesive coating.

PROPERTIES			
Total thickness micron	40 micron	Total thickness mils	1.540 mils
Business	Consumer Industrial Professional	Industry	Bundling Carton Sealing Splicing
Backing Type	BOPP	Backing thickness micron	24 micron
Adhesive type	Synthetic Rubber	Color	Tan
Tensile strength kg/cm	3,93 kg/cm	Elongation at break	165 %
Adhesion to steel g/cm	489,5 g/cm	Rolling ball test (RBT) cm	<2 cm
Shear on cardboard	>13.34 hours	Backing thickness mils	0.960 mils
Tensile strength lb./inch	22.000 lb./inch	Adhesion to steel oz./inch	44 oz./inch
Rolling ball test (RBT) inch	<0.78 inch	Service Temperature F° (Min / Max)	30/140 °F
Service Temperature C° (Min / Max)	(-2)/60 °C	Application Temperature F° (Min / Max)	54/110 °F
Application Temperature C° (Min / Max)	(12)/43 °C	Available width	72.000 mm 48.000 mm
Available length	66.000 m 132.000 m 200.000 m 50.000 m 100.000 m 150.000 m	Packaging type	6 roll flat pack