



Sustainable Solutions for Health, Productivity and the Environment.



Enviro Care[®] Novus

Multi-Surface Floor Coating



Enviro Care Novus

Multi-Surface Floor Coating

Where to Use

Enviro Care Novus creates a new standard in floor care by combining an unequaled level of environmental preference with performance, which surpasses conventional floor finish technology. Excels with all maintenance systems: scrub and recoat, spray buff or burnish. You'll get a tough, black-mark resistant shine with no powdering. No sealer is required on resilient flooring, even after heavy stripping. Use on vinyl, laminate, marble, linoleum, rubber, brick, stone, terrazzo, and bamboo floors.

Benefits

- Neutral pH
- No Suspected Endocrine Disruptors
- No Heavy Metal Complexes, APE's, Formaldehyde
- No Odor
- Phthalate Free
- Rapid dry time between coats
- 4000 plus sq ft coverage

Directions for Use

Floor preparation: For best results, start with a properly prepared floor by removing all of the old finish using Enviro Care Floor Stripper according to its directions. Rinse floor thoroughly to remove all residues and allow to dry.

Application:

Do not apply product if flooring and/or ambient temperatures are less than 55°F (13°C).

1. If not sealed, build an adequate base for ease of maintenance with the desired floor care system by applying three (3) thin coats of Enviro Care Novus. Allow adequate drying time between coats, typically 75°F (24°C) and 50% relative humidity requires an average of 45 minutes. Adjust drying times according to specific application conditions.
2. For added depth of gloss and protection, burnish floor, apply an additional one to two thin coats. If applying thick coats allow 24-48 hours dry time before applying additional coats.

Maintenance

Enviro Care Novus is an environmentally preferable zinc-free coating that may be attacked or dulled by harsh cleaners.

1. Damp mop or autoscrub using 1/2 oz per gallon/15 ml per 3.8 litres of Enviro Care Low Foam All Purpose Cleaner.
2. Recommend using aqua pad with burnishing machine, for gloss restoration.
3. Deep-scrub as required to maintain finish and gloss.
4. Daily dust mopping or sweeping to remove abrasive debris may impact

Distributor Contact Info

appearance and increase maintenance.

Coverage: 3500-4000 sq ft per gallon/280-370 sq m per 3.8 litres.

Slip Resistance: Meets ASTM D2047-93 requirements for slip resistance.

For a more detailed application and maintenance program please ask for our Step by Step Green Procedures Guide - Form 4105.

Properties	
Color	Opaque White
Fragrance	Mild
Viscosity	<10
VOC's (% by weight) EPA Method 24	0%
pH	8.6
Readily Biodegradable	Yes
Phosphate Free	No

Available Packages	Package Code	
2x2.5 gallon (2x9.5 litre) case	# 11927046	
4x1 gallon (4x3.8 litre) case	# 11927027	
55 gallon (208.2L) drum	# 11927057	

For handling and precautionary information, reference the product label and safety data sheet.

For more information about RMC call 1.800.836.1633 or go to www.rochestermidland.com