

HP-PLUS- FLOOR DRYING PACKAGE



SPECS

DATA	U.S./CAN DETAILED INFO
Model No.	HP-PLUS
Weight of HP60	70 lbs.
Total System Airflow	120 CFM (cubic feet per minute)
Static Pressure (Maximum)	60" (water lift) and still has 55 CFM
Housing Material	MDPE - med. density polyethylene
Motor Type	Industrial Regenerative Blower
Power Draw - 115v	15A circuit needed :12 amps
Drying Modes	Either Negatively or Positively

Designed for floor and ceiling drying using the HP-Plus system in the negative mode. The set-up is extremely quick, easy & efficient for your typical floor drying needs. Several decibels quieter than even the quiet HP60, no breaker tripping problems, consistent pressure with no need for pressure relief valves. Purchase accessories to increase your system's capabilities by purchasing Vac-It Panels (patent pending).

ORDER

HP-PLUS-FDP

ITEM DESCRIPTION	QTY	ORDER #
HP-PLUS Unit	1	
Main AIR IN - Quick Connects installed at factory	1	PTFC-PU
Main AIR OUT - Quick Connects installed at factory	1	PTMA-PU
AIR OUT Main Hose - 6' NO PRV REQUIRED	1	AOMH-PU
AIR IN Main Hose - 6' Inline Filter NO PRV REQUIRED	1	AIMH-PU
Carry Bag	1	CB3
Rolling Duffle Bag	1	CB2
Safety Yellow Blank Hose 1 1/2"x50'	2	PLO3
Quick Connect - Panel T's (Hosecuffs attached)	7	VAC-T
Quick Connect - 1 1/2" Hosecuff	14	HC3
Quick Connect Inline Manifold	6	QCM01
End Cap Plug	7	QCEP01
Variety Panel Package: (6) Large Multi Port Panels, (1) 8 Point, (1) Large Clear, & (1) U Panel Kit which includes (1) U Panel & (3) Small Panels w/ 3/8" Port	1	VACITPA-VP
Roll of Tubing	1	RHO5A
Soft Tubing Stoppers (bag of 40)	1	RP2
Silencer	1	SILENCER
Manual	1	

FLOOR DRYING EXAMPLES



Drying floors and ceilings

